TerrassenFix® II TF

SIHGA



TerrassenFix® II TF made from polyethylene



SIHGA® Feature	YOUR Benefit
universal constructive wood protection for terraces	creates distance between the woods*, thereby allowing them to breathe and increasing the lifespan
developed, patented and made in Austria	top European quality, experience from more than 14 years of terrace construction included
TerrassenFix® II TF with ∅ 70 mm is only placed on the substructure	saves time, no installation work
joint setting for 4, 5, 6, 7, 8, 9 mm wide joints without residue in the joint	joint widths can be adjusted quickly as a result; time-saving, practical, precise, all accessories enclosed
including TerrassenFix®II rods TFS and installation instructions	the TerrassenFix® II rods TFS cannot fall into the joints
TerrassenFix® II rods TFS are removed entirely using a handle, can be reused after screw-connecting the planks	nothing blocks the planks during their swell and shrinkage behaviour
monitored production from polyethylene	remains permanently dimensionally stable, is heat-, frost- and UV-resistant
calculation of quantity per m²	1: substructure distance [m]: width of terrace planks + joint [m]

SIHGA®		**Dimension**	**Average**
montagepack		TerrassenFix®	Quantity /m²
Art. No.	PU	Type	Stk.
40506	100	**II TF**	14

* calculation takes place with the assumption "plank width 140 mm".





SIHGA® TIP:

The joint space should not be less than 7 mm or 6 % of the plank width.