TerrassenFix® II Set TFL

SIHGA® Feature	YOUR Benefit
patented constructive wood protection as a set with L-GoFix® MS screws for terraces	the practical set for visible terrace plank fastening with very long lifespan
L-GoFix® MS made from hardened stainless steel	rust-free fastening, extremely break-proof
including SIHGAFIX® stainless steel, TerrassenFix® II rods TFS, Systemstift® and installation instructions	time-saving, practical, precise, all accessories enclosed; SIHGAFIX® stainless steel prevents rust from external sources and also screws into deep grooves
calculation of quantitiy	SIHGA® performs the calculation for you

SIHGA® montagepack		Dimension TerrassenFix® II	Planks Thickness	Set - Screw L-GoFix® MS	Sufficient for approx.
Art. No.	PU	Type	[mm]	∅ x Length	[m²]
40526	100	**TFL 60**	20	5,0 x 60	7,5
40546	100	**TFL 70**	24	5,0 x 70	7,5
40566	100	**TFL 80**	28	5,0 x 80	7,5
40576	100	**TFL 90**	32	5,0 x 90	7,5



TerrassenFix® II TF



L-GoFix® MS

SIHGA® TIP:

The joint distance should not be less than 7 mm or 6 % of the plank width, note design recommendations.

ETA-11/0425